



#### **Product Data Sheet**

# Y33/YV33 Type 3 Valve Manifold





The 'Y33' and 'YV33' Type 3 valve manifolds are designed for remote mounting to differential pressure transmitters, with separate isolation for LP and HP inlets plus equalising valve for simple calibration. Each needle valve head is designed for safe and reliable isolation, giving bubble tight shut off, with non-rotating & anti-galling tip and dynamic self-adjusting spindle seal to give long service life in a variety of service conditions.

| Part No. | Connections<br>Size | Α   | В   | C   | Weight<br>(Kgs) |
|----------|---------------------|-----|-----|-----|-----------------|
| Y33      | ½" F x F            | 8.4 | 3.6 | 2.5 | 1.5             |
| YV33     | ½" F x F            | 8.4 | 3.6 | 2.5 | 1.5             |

## **Key Features of the Oliver Needle Valve range**

- Non rotating tip self centering & anti-galling
- Piston ring gives dynamic adjustment of gland seal in response to pressure change
- Anti-blow out spindle a major safety feature
- Secure seal precision machined to give leak free operation for the life of the valve. Available in either PTFE or graphite foil

#### **Standard Specification**

|                                   | Pressure: 6000psi | Packing: PTFE           | Handle: T-Bar          | Bore: 0.21" (5.4mm) |
|-----------------------------------|-------------------|-------------------------|------------------------|---------------------|
|                                   | Temp: 240 deg C   | Thread form: NPT        | Seat: Metal to metal   | CV: 0.46            |
| 1/2" Inlet and Outlet Connections |                   | 1/4" NPT Plugged Vent C | onnection (on YV only) |                     |

### Ordering Code

| Οı | dering Code  |       |   |   |    |   |    |
|----|--|-------|---|---|----|---|----|
|    | $\mbox{(Typical example)} \rightarrow \mbox{Type}$   | Y33   | S | 1 | ВТ | 1 | AT |
|    | Y33 - Female x Female<br>YV33 - Female x Female with vents                                   |       |   |   |    |   |    |
|    | Material   |       |   |   |    |   |    |
|    | S - 316S31 Stainless Steel<br>M - Monel (400)<br>HC - Hastalloy (C276)<br>(Others available) |       |   |   |    |   |    |
|    | Optional Connections (NPT Stan   | dard) |   |   |    |   |    |
|    | BT - BSP Taper<br>BP - BSP Parallel<br>FSW - Female Socket Weld                              |       |   |   |    |   |    |
|    | Options  |       |   |   |    |   |    |

AG - Graphite Foil AT - Anti-Tamper

BKTC - Carbon steel mounting bracket BKTS - Stainless steel mounting bracket

HL - Handle Locking

HL-PI - Handle Locking + Position Indicator

HW - Hand Wheel

LT100 - Cryogenic Head Unit (-100°C)

MT - Metering Tip

MTG - Tapped Mounting Holes x 2

NA - NACE MR-01-75 (latest revision)

OXY - Oxygen Cleaned

PK - PEEK Soft Tip

2H - Straight through mounting holes

Rev 1.2



